

PalPower Micro 1kVA UPS

Specifications at a glimpse

Line Interactive UPS

Extended backup time through 2 built-in Batteries 7Ah

(1 battery only in the competition)

4 Universal output connectors for ease of use & connection of any device.

USB Interface for Shutdown software (Old RS232 in the competition)

1 year warranty on the UPS and batteries

Provided UPS & batteries are used in standby condition under normal charge/discharge battery cycles.



MICROPOWER SERIES Technical Specifications

		Micro 1000
Capacity (VA/Watts)	1000 / 600	
INPUT		
Nominal input voltage	110/120 Vac or 220/230/240 Vac	
Operating voltage range	81 ~ 145 Vac / 162 ~ 290 Vac	
Operating frequency range	50/60 Hz (± 10%)	
OUTPUT		
Output voltage range (Batt. Mode)	Simulated sine wave at nominal voltage ± 10%	
Frequency range (Batt. Mode)	50 or 60Hz ± 1Hz	
Transfer time	Typical 2~6 ms, 10ms max.	
BATTERY		
Battery type & number	12V/7Ah x 2	
Typical recharge time	6~8 hours (to 90% of full capacity)	
SYSTEM FEATURES		
Protection	Overload and overcharge protection	
Communication interface	USB/RS-232 (optional), Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC	
ENVIRONMENTAL		
Operating temperature	0 ~ 40 °C	
Humidity range	0 ~ 95% (non-condensing)	
Noise level	<40dB (1 meter from surface)	
PHYSICAL		
Dimension D × W × H (mm)	338 × 149.3 × 162	

Specifications are subject to change without prior notice.

MEMOPOWER under the brand PalPower is specially manufactured for Palpower energy & contracting co. Ltd

based on specific high quality standards.