

## PalPower Micro 2kVA UPS

### Specifications at a glimpse

Line Interactive UPS

Extended backup time through 2 built-in Batteries 9Ah

(1 battery only in the competition)

4 Universal output connectors for ease of use & connection of any device.

USB Interface for Shutdown software (Old RS232 in the competition)

1 year warranty on the UPS and batteries

Provided UPS & batteries are used in standby condition under normal charge/discharge battery cycles.



## MICROPOWER SERIES Technical Specifications

MODEL	Micro 2000
Capacity (VA/Watts)	2000 / 1200
<b>INPUT</b>	
Nominal input voltage	110/120 Vac or 220/230/240 Vac
Operating voltage range	81 ~ 145 Vac / 162 ~ 290 Vac
Operating frequency range	50/60 Hz (± 10%)
<b>OUTPUT</b>	
Output voltage range (Batt. Mode)	Simulated sine wave at nominal voltage ± 10%
Frequency range (Batt. Mode)	50 or 60Hz ± 1Hz
Transfer time	Typical 2~6 ms, 10ms max.
<b>BATTERY</b>	
Battery type & number	12 V/9Ah x 2
Typical recharge time	6~8 hours (to 90% of full capacity)
<b>SYSTEM FEATURES</b>	
Protection	Overload and overcharge protection
Communication interface	USB/RS-232 (optional), Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC
<b>ENVIRONMENTAL</b>	
Operating temperature	0 ~ 40 °C
Humidity range	0 ~ 95%(non-condensing)
Noise level	<40dB (1 meter from surface)
<b>PHYSICAL</b>	
Dimension D × W × H (mm)	380 × 158 × 198

Specifications are subject to change without prior notice.

**MEMOPOWER under the brand PalPower is specially manufactured for PalPower energy & contracting co. Ltd based on specific high quality standards.**